

characteristics Cleanroom Stool 2 with castors

Article: 9468R artificial leather

Dimensions in mm

| | | |
|-------|----|---------|
| Seat: | H: | 460-630 |
| | B: | 400 |
| | T: | 400 |

Packing data

| | | |
|--------|----------------|------|
| Weight | kg | 7,0 |
| Volume | m ³ | 0,13 |



Base equipment

| | | Benefit |
|----------------------------|--|---|
| Suitability for cleanrooms | Air purity level 3 according to DIN EN ISO 14644-1 Air purity level 1 according to US-Fed St. 209E Sealed upholstery with special foam technology Materials that are suitable for use in clean rooms Smooth, sealed surfaces | Certified suitability for clean rooms It can be ensured that no particles are emitted The build-up of particles on the chair are avoided |
| Conductivity | The metal components have a conductive coating Volume conductive plastic parts The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm Conductive castors | Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection |
| Seat | Extra large seat with a diameter of 400 mm | Automatically encourages healthy posture and upright seating The round front edge of the seat prevents blocked circulation in the thighs |
| Finishes for seat | ESD synthetic leather upholstery: High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and easy-care Colour: black (2571) | The soft and comfortable upholstery provides a comfortable feel. However, damages caused by sharp parts can not be excluded. Ideal for the use in production and laboratory |
| Seat height | Stepless seat height setting from 460-630 mm supported by safety gas spring with protective cover | Seat height can be adapted to nearly 95% of all body sizes, the cover protects the gas spring from dust and dirt |
| Functions / Mechanism | Ring release | Height adjustment can be operated comfortable and easy in sitting position |
| Base | The chairs are supplied with a brilliantly polished and wearproof aluminium 5 star base | Very high stability, longevity |
| Castors | Conductive Dual-wheel safety castors with load-sensitive brakes, for hard floors as standard | Chairs are braked when not used which decreases the accident risk |
| Materials | The materials used are recyclable | Environmentally friendly |
| Standards | DIN EN ISO 14644-1 DIN 61340-5-1 DIN 68 877 German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001 Regulation EWG Nr. 1836/93 Environmental Management System DIN EN ISO 14001 | Certified suitability for clean rooms 100% ESD protection Procuring is insured |
| Warranty | 10 year long term warranty, 3 years full warranty | Guaranteed quality and high efficiency |